gti

EVS Executive Color Viewing Stations

Providing Tight Conformance to the ISO 3664:2009 Standard



Above left: EVS-3052 viewing station with one deep file drawer (IF-3052) and eight shallow flat file drawers (FD-3052). Above right: EVS-2028 with a height adjustable (at set-up) rolling floor stand (EVS-2028/FS).

GTI's EVS color viewing systems are ideal for inspecting and evaluating printed output in conference room, studio, and office environments.

EVS viewers utilize state-of-the-art electronic ballasts which are combined with GTI's Graphiclite T8 fluorescent lamps to produce superior light evenness, excellent rear wall illumination, and enhanced energy efficiency. The EVS's luminaire is positioned parallel to the floor and utilizes an asymmetrical lens design which directs light at an angle ensuring consistent illumination on the work surface and rear wall.

Five EVS model sizes and a range of options are available.

EVS Features Include:

- ISO 3664:2009 compliance
- D50 light quality
- GTI Graphiclite 100 lamps
- Asymmetrical lens design
- LiteGuard II lamp usage monitor
- Horizontal and vertical viewing positions
- Spectrally neutral, non-yellowing diffusers
- Munsell N8/Gray viewing surfaces
- Print bar
- A range of storage and floor stand options

Soft Proofing Options

Soft proofing provides an opportunity to shorten the production cycle, while improving communications between color image service providers and their clients. GTI offers two EVS soft proofing solutions.

For accounts in need of standard dimming capability, manually operated digital dimming models are offered.

For automated soft proofing, GTI's EVS/iQ systems provide the features required for accurate soft proofing, including automatic matching of illumination in the viewing booth to the monitor. EVS/iQ soft proofing models also include digital dimming, a floor stand with casters, side walls, single or dual LCD monitor mounting, a keyboard drawer, and D50 lamps.

Contact GTI to learn more about soft proofing.

Below left: iQ control module and iQ sensor. Below right: EVS/iQ viewing area. A GTI iQ enabled viewer removes the manual processes and guesswork from viewer to monitor luminance matching and



graphic**lite**®



EVS Executive Color Viewing Stations

Accurate Color Viewing and Proofing of Printed Output

EVS Viewing Area Sizes

Model	EVS-2028	EVS-2540	EVS-3052	EVS-30106	EVS-4052
Viewing Area	20"×28"	25"×40"	29"×52"	29"×106"	40"×52"
$D \times W$	51 cm × 71 cm	64 cm × 102 cm	$74 \mathrm{cm} \times 132 \mathrm{cm}$	74 cm \times 269 cm	$102 \text{ cm} \times 132 \text{ cm}$

Options

EVS viewing stations can be ordered with height-adjustable floor stands or as countertop units. A range of storage options is available including flat file sets consisting of eight drawers, two door storage cabinets, one deep drawer, or two shallow file drawers.

Optional side walls are also available for EVS viewers.

See ordering guides to create the configuration you require for your viewing needs.



Above Left: An EVS-3052/FS viewing station with a height adjustable (at set-up) rolling floor stand and side walls (SW-EVS). Above Right: An EVS-30106 viewing station with two shallow flat file drawers (2F-3052) and two-door storage cabinet (SC-3052) on left, and one deep flat file drawer (1F-3052) and eight shallow flat file drawers (FD-3052) on right.

EVS Specifications

Model	Description	Dimensions $H \times W \times D$	Electrical
EVS-2028	Countertop Model	37" × 30" × 21.5" (94 cm × 76 cm × 55 cm)	90 Watts
EVS-2028/FS	Floor Stand Model	$69"-85" \times 30" \times 21.5" (175-216 \text{ cm} \times 76 \text{ cm} \times 55 \text{ cm})$	90 Watts
EVS-2540	Countertop Model	$41" \times 42" \times 26.5"$ (104 cm \times 107 cm \times 67 cm)	156 Watts
EVS-2540/FS	Floor Stand Model	73"–89" \times 42" \times 26.5" (185 – 226 cm \times 107 cm \times 67 cm)	156 Watts
EVS-3052	Countertop Model	45.5" × 54" × 31" (116 cm × 137 cm × 79 cm)	168 Watts
EVS-3052/FS	Floor Stand Model	77.5"-93.5" × 54" × 31" (197-238 cm × 137 cm × 79 cm)	168 Watts
EVS-30106	Countertop Model	45.5" × 108" × 31" (116 cm × 274 cm × 79 cm)	336 Watts
EVS-30106/FS	Floor Stand Model	77.5"-93.5" \times 108" \times 31" (197-238 cm \times 274 cm \times 79 cm)	336 Watts
EVS-4052	Countertop Model	45.5" × 54" × 41" (116 cm × 137 cm × 104 cm)	202 Watts
EVS-4052/FS	Floor Stand Model	77.5" – 93.5" × 54" × 41" (197 – 238 cm × 137 cm × 104 cm)	202 Watts

GTI is a leading manufacturer of tight tolerance lighting systems for critical color viewing, color communication, and color matching. An in-house spectroradiometric laboratory and a 100% measurement and verification production process guarantees that precision and accuracy is built into all products. All products are shipped with a certificate of product conformance (NIST traceable).



GTI Products Distributed By



Correct-Touch Graphic Arts

4349 Old Santa Fe Road Phone: San Luis Obispo, CA 93401 Email:

www.ctgraphicarts.com Phone: 877,820,6301

Email: info@ctgraphicarts.com